

## ► **INSTALLATION PRODUCTS**

### **HR 音箱系列**

#### **12" TWO-WAY SPEAKER SYSTEM** **单12"两分频全音域音箱**

FREQUENCY RANGE	频率响应	70-20KHz ( -10dB )
POWER HANDLING	标称功率	250W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY ( dB/1m1w )	灵敏度	97dB
NOMINAL DISPERSION	散射角度	90° × 40°
DRIVER COMPLEMENT	单体组合	12" Cone Driver 1" Dome Tweeter
DIMENSIONS ( H*W*D )	箱体尺寸	640 × 405 × 405mm
NET WEIGHT	净重	39kg

The HR-122 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker complement consists of an 12" LF woofer in a ported sub-enclosure, and a single 1" compression driver mounted on a 90° × 40° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loudspeaker complement.



**HR-122**

#### **15" TWO-WAY SPEAKER SYSTEM** **单15"两分频全音域音箱**

FREQUENCY RANGE	频率响应	40-20KHz ( -10dB )
POWER HANDLING	标称功率	350W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY ( dB/1m1w )	灵敏度	98dB
NOMINAL DISPERSION	散射角度	90° × 40°
DRIVER COMPLEMENT	单体组合	15" Cone Driver 1" Dome Tweeter
DIMENSIONS ( H*W*D )	箱体尺寸	840 × 505 × 505mm
NET WEIGHT	净重	50kg

The HR-152 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker complement consists of an 15" LF woofer in a ported sub-enclosure, and a single 1" compression driver mounted on a 90° × 40° horn. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, dadoed for strength and durability. Integrated eyebolt receptacles are located on the top of the system to facilitate a vertical installation. Perforated steel is employed for frontal protection of the loudspeaker complement.



**HR-152**

#### **DUAL 15" TWO-WAY SPEAKER SYSTEM** **双15"两分频全音域音箱**

FREQUENCY RANGE	频率响应	40-20KHz ( -10dB )
POWER HANDLING	标称功率	700W
NOMINAL IMPEDANCE	标称阻抗	4 ohm
SENSITIVITY ( dB/1m1w )	灵敏度	99dB
NOMINAL DISPERSION	散射角度	90° × 40°
DRIVER COMPLEMENT	单体组合	15" Cone Driver 1" Dome Tweeter
DIMENSIONS ( H*W*D )	箱体尺寸	1240 × 505 × 505mm
NET WEIGHT	净重	70kg

The HR-252 is a 2-way full range system in a computer optimized enclosure. Loudspeaker complement consists of twin proprietary midrange 15"s, individually loaded into separate subcompartments, and a single 1" compression driver mounted on a 90° × 40° horn. The enclosure is constructed of durable 18mm void-free MDF laminate, dadoed for strength and durability. Perforated steel is employed for frontal protection of the loudspeaker complement.



**HR-252**