



MK 系列KTV功率放大器

MK-300A

KTV前后级智能功放



新型ECHO混响效果线路
RETURN.SEND功能,方便外接讯号处理设备
优秀线路设计,最适合长时间满负荷工作
独立三段MIC音调,适应不同话筒使用
自动还原复位升降调功能

MODEL

MK-300A

POWER OUTPUT OR OUTPUT LEVEL/IMPEDANCE	100W/8 OHMS Per channel minimum RMS. Dynamic power output 120W+120W/8 OHMS
ECHO CONTROL	ECHO/DELAY/REPEAT
TOTAL HARMONIC DISTORTION	OUTPUT 0.2%
DAMPING FACTOR	25,at 50Hz
FREQUENCY RESPONSE	20HZ-20KHZ+1dB
SIGNAL-TO-NOISE RATIO (IEC-A)	VCR/CLD/TV/TUNER/TAPE,95dB
MAXIMUM INPUT LEVEL FOR MIC	100nv T.H.D.0.1%at 1KHz(RMS)
KEY CONTROLLER BOOST/CUT RANGE	#1~#8,0,b1~b8
POWER CONSUMPTION	220v AC 50/60HZ
DIMENSIONS (W × H × D)	482 × 132 × 426mm

MK-60A

KTV前后级智能功放



新型ECHO混响效果线路
RETURN.SEND功能,方便外接讯号处理设备
优秀线路设计,最适合长时间满负荷工作
独立三段MIC音调,适应不同话筒使用
自动还原复位升降调功能

MODEL

MK-60A

POWER OUTPUT OR OUTPUT LEVEL/IMPEDANCE	200W/8 OHMS Per channel minimum RMS. Dynamic power output 220W+220W/8 OHMS
ECHO CONTROL	ECHO/DELAY/REPEAT
TOTAL HARMONIC DISTORTION	OUTPUT 0.2%
DAMPING FACTOR	25,at 50Hz
FREQUENCY RESPONSE	20HZ-20KHZ+1dB 200Watts minimum RMS into 8 ohms load
SIGNAL-TO-NOISE RATIO (IEC-A)	100nv T.H.D.0.1%at 1KHz(RMS)
MAXIMUM INPUT LEVEL FOR MIC	100nv T.H.D.0.1%at 1KHz(RMS)
KEY CONTROLLER BOOST/CUT RANGE	#1~#8,0,b1~b8
POWER CONSUMPTION	220v AC 50/60HZ
DIMENSIONS (W × H × D)	482 × 132 × 426mm

MK-80A

三通道前后级智能KTV



独立低音功率输出,带可调分频网络
新型ECHO混响效果线路
RETURN.SEND功能,方便外接讯号处理设备
优秀线路设计,最适合长时间满负荷工作
独立三段MIC音调,适应不同话筒使用
自动还原复位升降调功能

MODEL

MK-80A

POWER OUTPUT OR OUTPUT LEVEL/IMPEDANCE	200W/8 OHMS Per channel minimum RMS. Dynamic power output 220W+220W/8 OHMS
SUB CHANNEL MONO OUTPUT	500Watts minimum RMS into 8 ohms load
ECHO CONTROL	ECHO/DELAY/REPEAT
TOTAL HARMONIC DISTORTION	OUTPUT 0.2%
DAMPING FACTOR	25,at 50Hz
FREQUENCY RESPONSE	20HZ-20KHZ+1dB
SIGNAL-TO-NOISE RATIO (IEC-A)	VCR/CLD/TV/TUNER/TAPE,95dB
MAXIMUM INPUT LEVEL FOR MIC	100nv T.H.D.0.1%at 1KHz(RMS)
KEY CONTROLLER BOOST/CUT RANGE	#1~#8,0,b1~b8
POWER CONSUMPTION	220v AC 50/60HZ
DIMENSIONS (W × H × D)	482 × 132 × 426mm

MK-90A

内置中置功率三通道KTV功放



新型ECHO混响效果线路
RETURN.SEND功能,方便外接讯号处理设备
优秀线路设计,最适合长时间满负荷工作
独立三段MIC音调,适应不同话筒使用
自动还原复位升降调功能
独立中置通道RMS 200W功率输出、连接中置音箱
独立低频讯号输出、带可调分频网络

MODEL

MK-90A

POWER OUTPUT OR OUTPUT LEVEL/IMPEDANCE	200W/8 OHMS Per channel minimum RMS. Dynamic power output 220W+220W/8 OHMS
CENTER CHANNEL MONO OUTPUT	200Watts minimum RMS into 8 ohms load
ECHO CONTROL	ECHO/DELAY/REPEAT
TOTAL HARMONIC DISTORTION	OUTPUT 0.2%
DAMPING FACTOR	25,at 50Hz
FREQUENCY RESPONSE	20HZ-20KHZ+1dB
SIGNAL-TO-NOISE RATIO (IEC-A)	VCR/CLD/TV/TUNER/TAPE,95dB
MAXIMUM INPUT LEVEL FOR MIC	100nv T.H.D.0.1%at 1KHz(RMS)
KEY CONTROLLER BOOST/CUT RANGE	#1~#8,0,b1~b8
POWER CONSUMPTION	220v AC 50/60HZ
DIMENSIONS (W × H × D)	482 × 132 × 426mm