

OMAR 专业调音台

PMX-100A



Low noise and low distortion 低噪音、低失真,
Digital echo with digital indicator 专业数字混响,数码显示
9 Bands graphic equalizer 双9 段图示均衡

10 Channels , 2 groups digital echo with digital indicator dual 9 bands graphic equalizer

10路2编组, 数字混响, 数码显示, 双9段均衡调音台

INPUT SENSITIVITY 输入灵敏度	MIC STEREO CH.INPUT AUX,SEND,RETURN	-60dB -40dB -20dB
S/N RATIO 信噪比		110dB
THD 失真度		0.02%
FREQ REPOSE 频率响应		20Hz-20KHz 0/-1dB
OUTPUT VOLTAGE 输出电压		4V MAX
HEADPHONES 耳机输出		7V/220 OHMS
PARAMETRIC EQ 参量均衡	HI MID LOW	+/-15dB 10KHz +/-15dB 250Hz-6KHz +/-15dB/60Hz
GROUPS 编组数		2
DIGITAL ECHOES 数字混响		16 STEPS IN EVERY 12.3 MS INCREASEMENT,200ms MAX
GRAPHIC EQUALIZER 图示均衡器		63Hz,125Hz,250Hz,500Hz, 1KHz,2KHz,4KHz,8KHz,16KHz

MC-102



MIC preamplifier with ultra-low noise 低噪音话筒前置放大器
3-Band EQ on MIC/LINE channels 话筒/线路通道3段均衡
Shtereo master outputs with XLR&1/4 jacks 频响度的声像控制
2-Guroup outputs 2路编组输出
2-Channel of AUX SEND RETURN 2路辅助输出返回
4-Channels output level indicator 4路输出电平指示

10Channels 2 groups professional mixer
10路2编组L100长推子专业调音台

INPUT SENSITIVITY 输入灵敏度	MIC STEREO CH.INPUT AUX,SEND,RETURN	-60dB -40dB -20dB
S/N RATIO 信噪比		110dB
THD 失真度		0.02%
FREQ REPOSE 频率响应		20Hz-20KHz 0/-1dB
OUTPUT VOLTAGE 输出电压		4V MAX
HEADPHONES 耳机输出		7V/220 OHMS
PARAMETRIC EQ 参量均衡	HI MID LOW	+/-15dB 10KHz +/-15dB 250Hz-6KHz +/-15dB/60Hz
GROUPS 编组数		2

MC-162



MIC preamplifier with ultra-low noise 低噪音话筒前置放大器
3-Band EQ on MIC/LINE channels 话筒/线路通道3段均衡
Shtereo master outputs with XLR&1/4 jacks 频响度的声像控制
2-Guroup outputs 2路编组输出
2-Channel of AUX SEND RETURN 2路辅助输出返回
4-Channels output level indicator 4路输出电平指示

16 Channels 2 groups professional mixer
16路2编组L100长推子专业调音台

INPUT SENSITIVITY 输入灵敏度	MIC STEREO CH.INPUT AUX,SEND,RETURN	-60dB -40dB -20dB
S/N RATIO 信噪比		110dB
THD 失真度		0.02%
FREQ REPOSE 频率响应		20Hz-20KHz 0/-1dB
OUTPUT VOLTAGE 输出电压		4V MAX
HEADPHONES 耳机输出		7V/220 OHMS
PARAMETRIC EQ 参量均衡	HI MID LOW	+/-15dB 10KHz +/-15dB 250Hz-6KHz +/-15dB/60Hz
GROUPS 编组数		2