

▶ INSTALLATION PRODUCTS

SF 音箱系列

SF-60

6.5" TWO-WAY SPEAKER SYSTEM

单6.5"两分频全音域音箱

FREQUENCY RANGE	频率响应	50-20KHz
POWER HANDLING	标称功率	100W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (dB/1m1w)	灵敏度	95dB
NOMINAL DISPERSION	散射角度	50-100° × 55°
DIMENSIONS (H*W*D)	箱体尺寸	370 × 210 × 230mm
NET WEIGHT	净重	7.3kg

The SF-60 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker complement consists of an 6.5"LF woofer in a ported sub-enclosure, and a single 1"compression driver mounted on a 50-100° × 55° rotatable waveguide. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, daddoed for strength and durability. Integrated eyebolt receptacles are located on the top and sides to facilitate installation. Perforated steel is employed for frontal protection of the loudspeaker complement.



SF-80

8" TWO-WAY SPEAKER SYSTEM

单8"两分频全音域音箱

FREQUENCY RANGE	频率响应	50-20KHz
POWER HANDLING	标称功率	180W
NOMINAL IMPEDANCE	标称阻抗	8 ohm
SENSITIVITY (dB/1m1w)	灵敏度	95dB
NOMINAL DISPERSION	散射角度	50-100° × 55°
DIMENSIONS (H*W*D)	箱体尺寸	505 × 240 × 230mm
NET WEIGHT	净重	12kg

The SF-80 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker complement consists of an 8"LF woofer in a ported sub-enclosure, and a single 1"compression driver mounted on a 50-100° × 55° rotatable waveguide. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, daddoed for strength and durability. Integrated eyebolt receptacles are located on the top and sides to facilitate installation. Perforated steel is employed for frontal protection of the loudspeaker complement.



SF-28

DUAL 8" TWO-WAY SPEAKER SYSTEM

双8"两分频全音域音箱

FREQUENCY RANGE	频率响应	50-20KHz
POWER HANDLING	标称功率	200W
NOMINAL IMPEDANCE	标称阻抗	4 ohm
SENSITIVITY (dB/1m1w)	灵敏度	95dB
NOMINAL DISPERSION	散射角度	50-100° × 55°
DIMENSIONS (H*W*D)	箱体尺寸	680 × 240 × 230mm
NET WEIGHT	净重	16.3kg

The SF-28 is a 2-way full range system in a trapezoidal, computer optimized enclosure. Loudspeaker complement consists of an 2x8"LF woofer in a ported sub-enclosure, and a single 1"compression driver mounted on a 50-100° × 55° rotatable waveguide. A factory optimized internal crossover is installed to ensure balanced output between the HF and LF components. The enclosure is constructed of durable 18mm void-free MDF laminate, daddoed for strength and durability. Integrated eyebolt receptacles are located on the top and sides to facilitate installation. Perforated steel is employed for frontal protection of the loudspeaker complement.

