

TA-330

MODEL

TA-330

OUTPUT POWER: (PER CHANNEL) CONTINUOUS AVERAGE OUTPUT BOTH CHANNELS DRIVEN 8 OHMS 4 OHMS	320W+320W 550W+550W
BRIDGED-MONO OPERATION 8 OHMS	800W
TOTAL HARMONIC DISTORTION	<0.05%
FREQUENCY RESPONSE	10HZ-20KHZ+/-1dB
DAMPING FACTOR 8 OHMS	>150
SLEW RATE	>30V/uS
S/N RATIO	>105dB
INPUT SENSITIVITY&IMPEDANCE	0dB (1v) 20KΩ
LED INDICATION	SIGNAL, BRIDGE, CLIP, PROTECT
DIMENSIONS (W x H x D)	482 x 89 x 445mm



High reliability and large output

Operating-load auto-recognized
System built-in, ensuring all the
Best optimized-operating status
With different speaker's impedance
Perfect protection circuit for short
cut, over temperature and overload

内置控制系统，保证高可靠
性，大功率输出
具有负载自动识别系统，短路
识别，不同负载识别，
保证机器在不同的负载下都处
于最佳的工作状态
具有完善的保护系统：短路保
护、过热保护、超载控制等

TA-660

MODEL

TA-660

OUTPUT POWER: (PER CHANNEL) CONTINUOUS AVERAGE OUTPUT BOTH CHANNELS DRIVEN 8 OHMS 4 OHMS	400W+400W 650W+650W
BRIDGED-MONO OPERATION 8 OHMS	1000W
TOTAL HARMONIC DISTORTION	<0.05%
FREQUENCY RESPONSE	10HZ-20HZ+/-1dB
DAMPING FACTOR 8 OHMS	>200
SLEW RATE	>30V/uS
S/N RATIO	>105dB
INPUT SENSITIVITY&IMPEDANCE	0dB (1v) 20KΩ
LED INDICATION	SIGNAL, BRIDGE, CLIP, PROTECT
DIMENSIONS (W x H x D)	482 x 89 x 445mm



High reliability and large output

Operating-load auto-recognized
System built-in, ensuring all the
Best optimized-operating status
With different speaker's impedance
Perfect protection circuit for short
cut, over temperature and overload

内置控制系统，保证高可靠
性，大功率输出
具有负载自动识别系统，短路
识别，不同负载识别，
保证机器在不同的负载下都处
于最佳的工作状态
具有完善的保护系统：短路保
护、过热保护、超载控制等

TA-990

MODEL

TA-990

OUTPUT POWER: (PER CHANNEL) CONTINUOUS AVERAGE OUTPUT BOTH CHANNELS DRIVEN 8 OHMS 4 OHMS	550W+550W 850W+850W
BRIDGED-MONO OPERATION 8 OHMS	1400W
TOTAL HARMONIC DISTORTION	<0.05%
FREQUENCY RESPONSE	10HZ-20HZ+/-1dB
DAMPING FACTOR 8 OHMS	>200
SLEW RATE	>30V/uS
S/N RATIO	>105dB
INPUT SENSITIVITY&IMPEDANCE	0dB (1v) 20KΩ
LED INDICATION	SIGNAL, BRIDGE, CLIP, PROTECT
DIMENSIONS (W x H x D)	482 x 89 x 445mm



High reliability and large output

Operating-load auto-recognized
System built-in, ensuring all the
Best optimized-operating status
With different speaker's impedance
Perfect protection circuit for short
cut, over temperature and overload

内置控制系统，保证高可靠
性，大功率输出
具有负载自动识别系统，短路
识别，不同负载识别，
保证机器在不同的负载下都处
于最佳的工作状态
具有完善的保护系统：短路保
护、过热保护、超载控制等